

# ClickShare C-5

Simple, one-click wireless presentation for huddle spaces



- **Entry-level wireless presentation model**
- **Content sharing with the ClickShare App and native BYOD**
- **100% secure, encrypted and cloud managed**

**Product specifications****CLICKSHARE C-5**

| <b>ClickShare Base Unit dimensions</b>                               |  |
|--|--|
| Dimensions (HxWxD)   | 34 mm x 135 mm x 135 mm  |
| Power supply   | Standard 110/220 V AC plug or USB-C (only Gen2)  |
| Power consumption  | Operational: 5-10W, 24W Max  |
| Weight   | 900 gr   |
| <b>General specifications</b>  |  |
| Operating system   | Windows 10 and higher macOS 11 (BigSur) and higher<br>Android v9 and higher (ClickShare App)*<br>iOS 12 and higher (ClickShare App)*                 |
| Video outputs  | 4K UHD (3840*2160) @ 30Hz. HDMI 1.4b or USB-C DisplayPort 1.2 (only Gen2)  |
| Audio output   | HDMI   |
| USB  | 1 X USB-A, 1 X USB-C   |
| ClickShare Buttons   | 0  |
| ClickShare App   | Desktop & Mobile   |
| Native protocols   | Airplay, Google Cast, Miracast   |
| Maximum number of simultaneous connections (with Buttons and/or App) | 32   |
| Noise Level  | Max. 25dBA @ 0-30°C<br>Max. 30dBA @ 30-40°C  |
| Authentication protocol  | WPA2-PSK in stand alone mode<br>WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode                                      |
| Wireless transmission protocol                                       | IEEE 802.11 a/g/n/ac and IEEE 802.15.1   |
| Reach  | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit<br>Frequency band 2.4 GHZ and 5 GHz |
| Frequency band   | 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries)   |
| Connections  | 1x Ethernet LAN 1Gbi<br>1x USB-C 2.0 (front); 1x USB-A 2.0 (front) -only Gen2: 1x USB-C 3.0 (front); 1x USB-A 3.0 (front)                            |
| Temperature range  | Operating: 0°C to +40°C (+32°F to +104°F)<br>Max: 35°C (95°F) at 3000m<br>Storage: -20°C to +60°C (-4°F to +140°F)                                   |
| Humidity   | Storage: 0 to 90% relative humidity, non-condensing<br>Operation: 0 to 85% relative humidity, non-condensing   |
| Anti-theft system  | Kensington lock  |
| Certifications   | FCC/CE   |
| Touch screen support & Interactivity                                 | /  |
| Room Dock (peripheral support)                                       | No   |
| Local view   | Local view of the room display only  |
| Network connection   | LAN & WiFi   |
| Management and reporting   | Yes  |
| Warranty   | 1 year standard. 5 years coverage via SmartCare  |
| *  | * depends on configuration, available in future firmware updates   |

**Last updated: 05 Mar 2024**

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.